



With the Superior® Vent-Free VFST-2 and VFPF-2 fireplaces, no venting is required, so you have tremendous design flexibility. Both units offer adjustable heat output, optional louvers and 99% fuel efficiency, delivering soothing warmth and year round comfort.



**VFST-2** shown with See-Through surround finished in a






F-2 VFST-2


### VF SEE-THROUGH/VF PENINSULA PRODUCT DIMENSIONS

# Front View Left End View\* Gas Line F Opening

# **Top View**



**Right Open View\*** 



\*From control side

	VFST-2	VFPF-2		VFST-2	VFPF-2
Α	42-3/4"	42-3/4"	I	31-3/4"	41-3/4"
В	37-1/4"	37-1/4"	J	4"	4"
С	20"	20"	K	24"	24"
D	34"	36"	L	5/8"	5/8"
Е	40"	40"	M	3-1/8"	3-1/8"
F	42"	-	N	18"	18"
G	5-1/2"	5-1/2"	0	-	20"
Н	4-1/2"	4-1/2"	Р	-	18"

# **BTU/HR CHART**

	Natural	Propane	
VFST-2	27,000 - 34,000	27,000 - 34,000	
VFPF-2	27,000 - 34,000	27,000 - 34,000	

### FRAMING DIMENSIONS

	Width	Height	Depth
VFST-2	43-1/4" Min.	43" Min.	22-3/4"
VFPF-2	40-1/8" Min.	43" Min.	22-3/4"

Distributed by:



©Lennox Industries Inc. 2009

Visit us at www.Lennox.com, or contact us at 1-800-9-LENNOX.

### **FEATURES AND BENEFITS**

Intricately detailed log set looks great on and off

Large, dramatic viewing portals present the active fire for impact in any setting

Vent-free design maximizes installation flexibility

Fail-safe ODS system provides safety and peace-of-mind

Natural gas and propane models means these models can go anywhere

99% fuel efficiency provides maximum heat at the best operating cost

Full complement of accessories allows these to be personalized to every taste

### **OPTIONAL ACCESSORIES**

Conversion Kits - PF to ST and ST to PF

Gas flex liner kit

Sealed tempered glass panel

Brass trim/hood

FAB-1100 blower

Arch door kit

Wall switch

Wireless remote

Wall thermostat

# **See-Through Surround**

The Charleston Poplar Surround is hand crafted using a combination of solid poplar and poplar veneer, so you can paint or stain this elegantly detailed surround. Assembly is simple with easy-to-use cam locks.



As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale - consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

Built to ANSI Z21.11.2 standard. Agency listings: OMNI Test Laboratories. Consult your distributor for local fireplace code information.



